

EN 1.4404(ASIS 316L) 材质或者等于的材质，表面硬化处理。

EN1.4404 (ASIS316L)是一种奥氏体Cr-Ni含Mo的不锈钢。为了降低产生碳化铬沉淀的危害，这种不锈钢有极低的含碳量。EN1.4404是一种最常用的不锈钢材质，用这种材质做的不锈钢垫圈适合无氯环境或者酸性环境。


规格表

型号	螺栓尺寸		Ø _i (mm)	Ø _o (mm)	厚度 T (mm)	最小包装 (对)	大约重量 (kg/100对)
	公制	美制					
NL3ss	M3	#5	3.4	7.0	2.2	200	0.04
NL3.5ss	M3.5	#6	3.9	7.6	2.2	200	0.04
NL3.5spss	M3.5	#6	3.9	9.0	2.2	200	0.07
NL4ss	M4	#8	4.4	7.6	2.2	200	0.04
NL4spss	M4	#8	4.4	9.0	2.2	200	0.07
NL5ss	M5	#10	5.4	9.0	2.2	200	0.06
NL5spss	M5	#10	5.4	10.8	2.2	200	0.11
NL6ss	M6		6.5	10.8	2.2	200	0.09
NL6spss	M6		6.5	13.5	2.0	200	0.16
NL1/4"ss		1/4"	7.2	11.5	2.2	200	0.09
NL1/4"spss		1/4"	7.2	13.5	2.2	200	0.15
NL8ss	M8	5/16"	8.7	13.5	2.0	200	0.12
NL8spss	M8	5/16"	8.7	16.6	2.0	200	0.22
NL3/8"ss		3/8"	10.3	16.6	2.0	200	0.19
NL3/8"spss		3/8"	10.3	21.0	2.0	200	0.38
NL10ss	M10		10.7	16.6	2.0	200	0.18
NL10spss	M10		10.7	21.0	2.2	200	0.37
NL11ss	M11	7/16"	11.4	18.5	2.2	200	0.26
NL12ss	M12		13.0	19.5	2.0	200	0.23
NL12spss	M12		13.0	25.4	3.0	100	0.82
NL1/2"ss		1/2"	13.5	19.5	2.0	200	0.24
NL1/2"spss		1/2"	13.5	25.4	3.2	100	0.80
NL14ss	M14	9/16"	15.2	23.0	3.0	100	0.49
NL14spss	M14	9/16"	15.2	30.7	3.2	100	1.31
NL16ss	M16	5/8"	17.0	25.4	3.0	100	0.59
NL16spss	M16	5/8"	17.0	30.7	3.2	100	1.13
NL18ss	M18		19.5	29.0	3.2	100	0.80
NL18spss	M18		19.5	34.5	3.2	100	1.56
NL3/4"ss		3/4"	20.0	30.7	3.2	100	0.96
NL3/4"spss		3/4"	20.0	39.0	3.2	100	2.10
NL20ss	M20		21.4	30.7	3.0	100	0.82
NL20spss	M20		21.4	39.0	3.2	100	2.06
NL22ss	M22	7/8"	23.4	34.5	3.2	100	1.23
NL22spss	M22	7/8"	23.4	42.0	3.2	50	2.23
NL24ss	M24		25.3	39.0	3.2	100	1.52
NL24spss	M24		25.3	48.5	3.2	50	3.50
NL1"ss		1"	27.9	39.0	3.2	100	1.42
NL1"spss		1"	27.9	48.5	3.2	50	3.22
NL27ss	M27		28.4	42.0	6.8	50	3.45
NL27spss	M27		28.4	48.5	6.8	25	5.85
NL30ss	M30	1-1/8"	31.4	47.0	6.8	50	4.43
NL30spss	M30	1-1/8"	31.4	58.5	6.8	25	9.53
NL33ss	M33	1-1/4"	34.4	48.5	6.8	25	4.25
NL36ss	M36	1-3/8"	37.4	55.0	6.8	25	5.96
NL39ss	M39	1-1/2"	40.4	58.5	6.8	25	6.74
NL42ss	M42		43.2	63.0	6.8	25	7.96
NL45ss	M45	1-3/4"	46.2	70.0	6.8	25	10.20
NL48ss	M48		49.6	75.0	6.8	25	12.00
NL52ss	M52	2"	53.6	80.0	9.0	25	20.10
NL56ss	M56	2-1/4"	59.1	85.0	9.0	10	21.30
NL60ss	M60		63.1	90.0	9.0	10	23.5
NL64ss	M64	2-1/2"	67.1	95.0	9.0	10	25.80
NL68ss	M68		71.1	100.0	9.0	1	28.20
NL72ss	M72		75.1	105.0	9.0	1	30.70
NL76ss	M76	3"	79.1	110.0	9.0	1	33.30
NL80ss	M80	3-1/8"	83.1	115.0	9.0	1	36.00

NL3ss - NL8ss
Ø_i ± 0.1mm

NL10ss - NL42ss
Ø_i ± 0.2mm


NL45ss - NL80ss
Ø_i + 0.5/-0.0mm



NL3ss - NL24ss
Ø_o ± 0.2mm

NL27ss - NL42ss
Ø_o ± 0.3mm


NL45 - NL80ss
Ø_o + 0.0/-2.0mm



NL3ss - NL24ss
T ± 0.25mm

NL27ss - NL42ss
T ± 0.0/-0.5mm

NL45ss - NL80ss
T ± 0.75mm



标准的不锈钢垫圈我们都有库存。

- 液压扳手
- 螺栓拉伸器
- 液压千斤顶
- 电动液压泵
- 气动液压泵
- 手动液压泵
- 液压拉马
- 法兰分离器
- 螺母破切器
- 电动扳手
- 系统元件
- 超级螺栓
- 防松垫圈